

A-30

Various Types of Baume Hydrometers

各種 — めっき用ボーメ

(Note) If calibration certificate is required, please buy the model with calibration certificate (except for Model -04). However we can prepare only Japanese version and extra cost is required.

(注)校正証明書(日本語のみ)の取得を希望される場合は、校正証明書付ボーメをお求めください。(ただし4型を除く)



Outer Size 外寸	200mm~300mm
Material 材質	Glass, Lead ガラス, 鉛

Product No. 製品番号	Product 製品名	Specification 仕様	Adequate Temperature 適正温度
A-30-01	Chromium Plating Baume Hydrometer クロムめっき用ボーメ	Chromic acid : 50 ~ 400g/L クロム酸 : 50 ~ 400g/L	15°C
A-30-02	Plating Hydrometer (Model-1) めっき用ボーメ (1型)	Baume Degree 0 ~ 20 Specific Gravity : 1.00 ~ 1.16 ボーメ 0~20度 比重1.00~1.16	15°C
A-30-03	Plating Hydrometer (Model-2) めっき用ボーメ (2型)	Baume Degree 15 ~ 35 Specific Gravity : 1.12 ~ 1.32 ボーメ 15~35度 比重1.12~1.32	15°C
A-30-04	Plating Hydrometer (Model-3) めっき用ボーメ (3型)	Baume Degree 30 ~ 50 Specific Gravity : 1.260 ~ 1.530 ボーメ 30~50度 比重1.260~1.530	15°C
A-30-05	Plating Hydrometer (Model-4) めっき用ボーメ (4型)	Baume Degree 0 ~ 70 Specific Gravity : 1.000 ~ 2.000 ボーメ 0~70度 比重1.000~2.000	15°C
A-30-06	Percent Hydrometer (Hydrochloric Acid) パーセントボーメ (塩酸)	0 ~ 25 Volume% Direct-reading Type 0~25容量% 直読式	20°C
A-30-07	Percent Hydrometer (Sulfuric Acid) パーセントボーメ (硫酸)	1 ~ 25 Volume% Direct-reading Type 1~25容量% 直読式	20°C
A-30-08	Percent Hydrometer (Sodium hydroxide) パーセントボーメ (苛性ソーダ)	1 ~ 25 Weight% Direct-reading Type 1~25重量% 直読式	20°C